

- Direct low noise synthesizer
- LCD user interface
- 10W output power



ΤΕΧΝΙΚΑ ΧΑΡΑΚΤΗΡΙΣΤΙΚΑ

Transmitter:

Frequency range: 1700-1710,1785-1800 MHz
Carrier power: 10W
Frequency control: Direct synthesis PLL
Frequency stability: 5ppm
Modulation: F3 FM
Output impedance: 50 Ohms
RF output connector: "N" female.
Audio input impedance: 10 K Ω
Audio input level: 0dBu
Limiting threshold: -5dBu
Audio input connector: BNC female.
Frequency response: 25 Hz- 70 KHz.
Power supply: 230 VAC +/- 10% 50 Hz
Power consumption: 100 W
Operating temperature range: 0-45 °C
Dimensions: 483mm x 132mm x 525mm
(19" Rack 3U)
Weight: 8 Kg.

Receiver:

Frequency range: 1700 -1710, 1785-1800 MHz
Frequency control: Direct synthesis PLL
Sensitivity: -60 dBm for 50dB SNR
Image rejection: >60 dB
Modulation: F3 FM
RF input impedance: 50 Ω
RF input connector: "N" female.
Audio output impedance: 10 K Ω
Audio output connector: BNC female.
Audio output level : 0dBu
Frequency response: 25 Hz- 70 KHz.
Power supply: 230 VAC +/- 10% 50 Hz
Power consumption: 50 W
Operating Temperature range: 0-45 °C
Dimensions: 483mm x 132mm x 525mm
(19" Rack 3U)
Weight: 7,5 Kg.

Τα χαρακτηριστικά μπορεί να αλλάξουν χωρίς προειδοποίηση.